

Grade 60507

High Density Polyethylene (HDPE)



Product Description

60507 is a HDPE injection molding grade which combines good flow ability with balanced physical properties. This resin is well suited for general purpose applications requiring high stiffness.

Application

- Crates
- Injection molding grade

PROPERTY	UNIT	TYPICAL VALUE	TEST METHOD
DENSITY	(g/ml)	0.958	ASTM D 1505
MFR(190°C/2.16KG)	(g/10min)	7.5	ASTM D 1238
TENSILE STRENGTH AT YIELD	(MPa)	30	ASTM D 638
TENSILE STRENGTH AT BREAK	(MPa)	13	ASTM D 638
ULTIMATE ELONGATION	(%)	350	ASTM D 638
FLEXURAL MODULUS	(MPa)	1500	ASTM D 790
NOTCHED IZOD IMPACT AT 23°C	(J/m)	36	ASTM D 256/A
VICAT SOFTENING POINT	(°C)	127	ASTM D 1525

Physical properties on compression molded specimen obtained according to ASTM D 1928c.

Producer: Jam Petrochemical Co.

Licensors: Basell

Packing: 25 Kg plastic bag

IMPORTANT: The information and data presented herein are based on values from respective product manufacture. Therefore, no warranty or guarantee, expressed or implied, is made nor is any accountability accepted with respect to the use of such information and data. All mentioned data are typical values and not to be considered as legally binding specification.